



# BIJOU GLOSSY

Wall Tile



 Exquite







7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY** White



7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY** Bone



7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY** Silver




7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY** Grey



7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY** Black



7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY**  
**WHITE BULLNOSE**  
(7,5 cm. Side)



7,5 x 30 cm (3" x 12")  
**BIJOU GLOSSY**  
**WHITE BULLNOSE**  
(30 cm. Side)



## PACKING INFORMATION

PRODUCT	THICKNESS	Pcs x Box	Sqm x Box	Sqft x Box	Kgs x Box	Lbs x Box	Box x Pal	Sqm x Pal	Sqft x Pal	Kgs x Pal	Lbs x Pal
7,5x30 (3"x12") Bijou Glossy	8,0 mm.-0,31"	44	1	10.76	14	30,86	72	72	774,72	1033	2278
7,5x30 (3"x12") Bijou Glossy Bullnose (7,5 cm Side)	8,0 mm.-0,31"	10	-	-	3,1	6,83	-	-			
7,5x30 (3"x12") Bijou Glossy Bullnose (30 cm. Side)	8,0 mm.-0,31"	10	-	-	3,1	6,83	-	-			

## GENERAL SPECIFICATIONS

		Serie: <b>BIJOU GLOSSY</b> Wall tiles Group BIII		MONTECERA
TECHNICAL FEATURES	NORMS	Requirement for Nominal Size N.		
		7 cm ≤ N < 15 cm	N ≥ 15 cm	
LENGTH AND WIDTH	EN ISO 10545-2	±0,75mm.	± 0,5% ±2,0mm	Confirmed
THICKNESS	EN ISO 10545-2	±0,5mm.	± 0,5%	Confirmed
STRAIGHTNESS	EN ISO 10545-2	±0,5mm.	± 0,5% ±1,5mm	Confirmed
SQUARNESS	EN ISO 10545-2	±0,75mm.	± 0,6% ±2,0mm	Confirmed
SURFACE FLATNESS	EN ISO 10545-2	±0,75mm.	± 0,5% ±2,0mm	Confirmed
WATER ABSORPTION	ASTM C373	E > 10%		E > 10%
MODULUS OF RUPTURE	EN ISO 10545-4	≥ 12N/mm <sup>2</sup>		≥ 15N/mm <sup>2</sup>
THERMAL SHOCK RESISTANCE	EN ISO 10545-9	Required		Resistant
CHEMICAL RESISTANCE	EN ISO 10545-13	Indicated by manufacturer		Resistant
RESISTANCE TO STAINS	EN ISO 10545-14	Indicated by manufacturer		Resistant
SHADE VARIATION	ANSI A137.1	Indicated by manufacturer		V1